

Authorised Dealer :



ARCHITECT'S FIRST CHOICE



HEAD OFFICE:

KOTA TAPES (INDIA) PVT. LTD.

303, Atlantis K-10, Opp: Swagat Petrol Pump,
Vikram Sarabhai Marg,
Wadiwadi, Vadodara-390023.

Cus. Care No. :+91 265-2355796, 2321166



BRANCH OFFICE:

KOTA INDUSTRIAL PRODUCTS PVT. LTD.

Off. 406, K. K. Arcade, 98, Narayan Dhruv Street,
Masjid Bunder, Mumbai - 3

Ph.: +91- 9825295431 / 9825320884

E-mail : kota@ptfetapeindia.com www.ptfetapeindia.com

CONNECTION TECHNIQUES FOR
PVC, UPVC AND CPVC PIPING SYSTEMS
MEETS ASTM STANDARD QUALITY REQUIREMENTS



IS 14182



CM/L-7200146304



SEAL TITE®



**In technical Collaboration with
INNOVATIVE ADHESIVE INC., USA**

SEALTITE® offers extensive specialty products to meet all your piping needs, including repair adhesives for leaking joints, pipe thread sealants and water-saving gasket lubricants, as well as test plugs for testing the integrity of DWV and sewer systems.

SEALTITE® offers the most extensive line of Primers and Cleaners for the piping industry. These products are used for the surface preparation of plastic pipe and fittings, which is necessary for the proper solvent welding of these materials. All SEALTITE® Primers and Cleaners are low VOC products, which are environmentally friendly with lower emissions and reduced odour, surpassing the most stringent regulations.* All SEALTITE® Primers and Cleaners are formulated for use on PVC and CPVC pipe and fittings, and our SEALTITE Cleaner can also be used on ABS and styrene piping applications.

KOTA group of companies is the pioneer and leading manufacturer of SEALTITE® solvent cements, primers and cleaners for PVC, CPVC, ABS, Epoxy Putty and other plastic piping systems. SEALTITE® products are globally-recognized as the premium products for joining plastic pipes and fittings. Headquartered at VADODARA, SEALTITE® has pan India presence of sales representatives and distribution net work.

Our Commitment

QUALITY POLICY

SEALTITE® delivers superior quality, environmentally friendly products and services to our customers. Continuous improvement of our people, products and processes is the responsibility of all employees. SEAL TITE has Provided reliable, high quality products for the Residential and commercial plumbing industries.



COMPLETE SELECTION GUIDE FOR SOLVENT CEMENT

PRODUCTS	PRODUCT CODE	COLOUR	TYPE	NOMINAL PIPE SIZE Diameter in Inch	PIPE FORMATE SCHEDULE
SEAL TITE CPVC	C-1315	Yellow	Medium Bodied	Up to 4"	Sch.40 & 80
	C-1310	Orange	Heavy Bodied	Up to 12"	Sch.40 & 80
	C-1317	Orange	Medium Bodied	Up to 4"	Sch.40 & 80
SEAL TITE UPVC (PVC-U)	U-1200	Clear/Blue	Regular Bodied	Up to 4"	Sch.40 & 80
	U-1204	Clear/Blue	Medium Bodied	Up to 6" Up to 4"	Sch.40 Sch. 80
	U-1210	Clear/Blue	Heavy Bodied	Up to 12"	Sch.40 & 80
SEAL TITE PVC (Irrigation)	P-1045	Clear	Regular Bodied	Up to 8"	Irrigation Pipes
SEAL TITE ABS	A-1415	Milky	Medium Bodied	Up to 8"	ABS Pipes
SEAL TITE PRIMER	PRIMER	Clear	Water Thin	More than 3"	Sch.40 & 80

* Can be used without a primer on non-pressure system

PTFE Seal Tape

We have achieved expertise in manufacturing and supplying **PTFE Seal Tape** which is tested for quality at each stage of production, such that flawless variety of Seal Tape can be supplied to the market. PTFE Seal Tape manufactured by the company is in demand for outstanding acid -resistant and alkali-resistant features. The range of PTFE Seal Tape is offered to the clients at competitive market prices within a predetermined time-frame in secured packing . We are the preferential choice for obtaining quality PTFE Seal Tape.



- Excellent acid-resistant
 - Alkali -resistant
 - Insulation of high and low temperature
 - Customized length, width & brand
 - Superior grade
- Industrial Suppliers
 - Pipe fitting Suppliers
 - Plumbing material Suppliers
 - Building material Suppliers

SEAL TITE



Specifications	
Width (mm)	12, 19, 25
Length (mtrs)	10
pH Range	0-14
Temperature	-240 c to +260 c
Pressure	170

TOPAZ



Specifications	
Width (mm)	12, 19, 25
Length (mtrs)	10
pH Range	0-14
Temperature	-240 c to +260 c
Pressure	170

WHITE GOLD



Specifications	
Width (mm)	12.5, 19, 25
Length (mtrs)	12
pH Range	0-14
Temperature	-240 c to +260 c
Pressure	170

RUBI



Specifications	
Width (mm)	12, 19, 25
Length (mtrs)	10
pH Range	0-14
Temperature	-240 c to +260 c
Pressure	170

COMET



Specifications	
Width (mm)	12, 19, 25
Length (mtrs)	10
pH Range	0-14
Temperature	-240 c to +260 c
Pressure	170

GALAXY



Specifications	
Width (mm)	12, 19, 25
Length (mtrs)	10
pH Range	0-14
Temperature	-240 c to +260 c
Pressure	170

VIVO



Specifications	
Width (mm)	12, 19, 25
Length (mtrs)	10
pH Range	0-14
Temperature	-240 c to +260 c
Pressure	170

GLAN



Specifications	
Width (mm)	12, 19, 25
Length (mtrs)	15
pH Range	0-14
Temperature	-240 c to +260 c
Pressure	170

KEN



Specifications	
Width (mm)	12, 19, 25
Length (mtrs)	15
pH Range	0-14
Temperature	-240 c to +260 c
Pressure	170



LUBRICANTS

SEAL TITE RUBBER LUBRICANT - ADHESIVE.

- Paste Type simple, For quick leak proof joining of PVC, SWR piping system.
- Bacteria free, Non Toxic, Non corrosive, Non flammable material, Does not contain Natural or Synthatic Rubber.
- Ideal for Potable water. Swear Drain, Piping systems Against non pressure Application.
- **Storage :** Store in Cool & Dry place at Room Temp. **Shelf Life : 1 Year**
- **Available in Packing :**

PACK SIZE	100 gm	250 gm	500 gm
UNITS PER CARTON	192	80	40

PIPE SEALENT

SEAL TITE LIQUID SEALANT – BLACK – WHITE ADHESIVE

- Quality Formulation for thread locking, Sealing. Bonding and Gasketing.
- Makes perfect excellent adhesion and bonding for leak proof pipe joining for All types of metal pipes and fittings. Ideal for Residential plumbing and Industrial Application.
- Withstand action of Hot & Cold water, Solvents such as Petrol, Oil, Kerosene, Chemicals such as salt solutions and Dilute Acids, Corrosive gases such as Sulphur Dioxide, Ammonia etc.
- **Storage :** Store in Cool & Dry place at Room Temp. **Shelf Life : 1 Year**
- **Available in Packing :**

PACK SIZE	50 gm	100 gm	200 gm	500 gm
UNITS PER CARTON	240	160	75	30



EPOXY PUTTY



K-Seal General Purpose Epoxy Compound (Putty)

K-SEAL GP is a two - component room temperature setting, multi purpose epoxy putty for Sealing of leakage, insulation of cable terminals. plumbing and non-plumbing applications. Sets in 60 minute. **Shelf Life : 18 Months**

PACK SIZE	30 g	60 g	100 g	1 kg
UNITS PER CARTON	560	240	200	20



K-Seal Super Fast Epoxy Compound (Putty)

K-SEAL SUPER FAST is Fast Curing, High Strength, multi-purpose two component epoxy putty for Automobile surfaces, Leakage repairs , Pattern making, plumbing and non-plumbing applications. Sets in 30 minute. **Shelf Life : 12 Months**

PACK SIZE	25 g	60 g	100 g
UNITS PER CARTON	560	240	200



K-Seal Sanitary White Epoxy Compound (Putty)

K-SEAL SANITARY is a multi-purpose white colour sealant. An alternate solution to white cement. It is used for filling gaps in bathrooms, kitchens, wash basin, wall tiles, Porcelain, air conditioner , water coolers.

Sets in 90 minute. **Shelf Life : 12 Months**

PACK SIZE	25 g	60 g	100 g
UNITS PER CARTON	560	240	200

SEAL TITE PVC, UPVC (PVC-U) SOLVENT CEMENT

UPVC (PVC-U) : U-1200

Clear / Blue - Regular Bodied - LOW VOC - Fast Setting Solvent Cement

- Quality Product Designed for all grades and types of PVC, UPVC pipes and Fittings through 3”(90 mm) Diameter, Schedule 40 & 80 interference fit.
- **Meets ASTM D-2564**, Brookfield Viscosity minimum- 90 cP at 27°C
- Application for Residential plumbing, Industrial , Pool & Spa, Irrigation, drain , waste & vent system, Electrical conduit, PVC foam core pipe.
- **Storage :** Store in Cool & Dry place at Room Temp. **Shelf Life : 3 Years**
- **Available in Packing :**

PACK SIZE	59 ml (2 OZ)	118 ml (4 OZ)	237 ml (8 OZ)	473 ml (16 OZ)	948 ml (32 OZ)
UNITS PER CARTON	288	144	96	48	24



UPVC (PVC-U) : U-1204

Clear / Blue - Medium Bodied - LOW VOC - Fast Setting - Heavy Duty Solvent Cement

- Quality Product Designed for all grades and types of PVC, UPVC pipes and Fittings through 6”(160 mm) dia. Schedule 40 & 4”(110 mm) Sch.80 interference fit.
- Primer is strongly recommended for more than 3” (90mm) diameter Pipe.
- **Meets ASTM D-2564, Certified by NSF International.** Brookfield Viscosity minimum- 500 cP at 27°C
- Application for Residential plumbing, Industrial, Pool & Spa, Irrigation, drain, waste & vent system, Electrical conduit, PVC foam core pipe.
- **Storage :** Store in Cool & Dry place at Room Temp.
- **Shelf Life : 3 Years**
- **Available in Packing :**

PACK SIZE	10 ml Tube	25 ml Tube	59 ml (2 OZ)	118 ml (4 OZ)	237 ml (8 OZ)	473 ml (16 OZ)	948 ml (32 OZ)
UNITS PER CARTON	800	600	288	144	96	48	24



UPVC (PVC-U) : U-1210

Clear - Heavy Bodied - LOW VOC - Fast Setting - Solvent Cement

- Quality Product Designed for all grades and types of PVC, UPVC pipes and Fittings through 12”dia. Including Schedule 80.
- It has good gap filling properties and its medium set allows more working time in Warm water.
- **Meets ASTM D-2564**, Brookfield Viscosity minimum - 1600 cP at 27°C
- Application for Residential plumbing, Industrial, Pool & Spa, Irrigation, Electrical conduit, PVC foam core Pipe and SWR System.
- Primer is strongly recommended for more than 3” (90mm) diameter Pipe
- **Storage :** Store in Cool & Dry place at Room Temp. **Shelf Life : 3 Years**
- **Available in Packing :**

PACK SIZE	59 ml (2 OZ)	118 ml (4 OZ)	237 ml (8 OZ)	473 ml (16 OZ)	948 ml (32 OZ)
UNITS PER CARTON	288	144	96	48	24



SEAL TITE CPVC SOLVENT CEMENT

CPVC : C-1310



Orange - Heavy Bodied - LOW VOC-

Medium Setting High Strength Solvent Cement

- Quality Product Designed for all types of CPVC pipes and Fittings interference fit. Through 12” dia. (315 mm) Schedules 40 and schedule 80.
- Primer is strongly recommended for more than 3” (90mm) diameter Pipe.
- Meets ASTM D-2846 and ASTM F-493, Brookfield Viscosity minimum - 1600 cP at 27°C
- Quality Formulation for Potable Hot and Cold water up to 180F (82C). Suitable for Residential and Industrial Plunbing.
- Storage : Store in Cool & Dry place at Room Temp. Shelf Life : 2 Years
- Available in Packing :

PACK SIZE	59 ml (2 OZ)	118 ml (4 OZ)	237 ml (8 OZ)	473 ml (16 OZ)	948 ml (32 OZ)
UNITS PER CARTON	288	144	96	48	24

CPVC : C-1315



Yellow - Medium Bodied - LOW VOC - Fast Setting Solvent Cement

- Leak proof pipe joining for all types of CPVC pipes and Fittings interference fit. Through 4” dia. (110 mm) Schedules 40 and schedule 80.
- Certified by NSF International for Compliance with ASTM D-2846 and ASTM F-493,
- Brookfield Viscosity minimum - 500 cP at 27°C
- Quality Formulation for Potable Hot and Cold water up to 180F (82C). Suitable for Residential and Industrial Plunbing.
- Storage : Store in Cool & Dry place at Room Temp. Shelf Life : 2 Years
- Available in Packing :

PACK SIZE	10 ml Tube	25 ml Tube	59 ml (2 OZ)	118 ml (4 OZ)	237 ml (8 OZ)	473 ml (16 OZ)	948 ml (32 OZ)
UNITS PER CARTON	800	600	288	144	96	48	24



CPVC : C-1317



Orange - Medium Bodied - LOW VOC - Medium Setting Solvent Cement

- Leak proof pipe joining for all types of CPVC pipes and Fittings interference fit. Through 4” dia. (110 mm) Schedules 40 and schedule 80.
- Premium, High Strength, Chemical Resistance cement for use with CPVC piping system carrying Acids, Base, Salts and Hypochloride.
- Meets ASTM D-2846 and ASTM F-493, Brookfield Viscosity minimum - 500 cP at 27°C
- Quality Formulation for Waste Water Plants.
- Storage : Store in Cool & Dry place at Room Temp. Shelf Life : 2 Years
- Available in Packing :

PACK SIZE	59 ml (2 OZ)	118 ml (4 OZ)	237 ml (8 OZ)	473 ml (16 OZ)	948 ml (32 OZ)
UNITS PER CARTON	288	144	96	48	24

SEAL TITE ABS SOLVENT CEMENT

ABS CEMENT : A - 1415

MILKY - Medium Bodied - Fast Setting High Strength ABS Solvent Cement

- Leak proof pipe joining for all classes pipes and Schedule of ABS pipe and Fittings Through 8” dia. (200 mm) interference fit.
- Meets ASTM D-2235, Brookfield Viscosity minimum - 500 cP at 27°C
- Application for plumbing (DWV, Sever & Drain), conduit, PVC foam core pipe.
- Storage : Store in Cool & Dry place at Room Temp. Shelf Life : 2 Years
- Available in Packing :

PACK SIZE	59 ml (2 OZ)	118 ml (4 OZ)	237 ml (8 OZ)	473 ml (16 OZ)	948 ml (32 OZ)
UNITS PER CARTON	288	144	96	48	24



IRRIGATION PVC SOLVENT CEMENT : P-1045

SEAL TITE – P 1045 – clear - pvc solvent cement

Clear – Regular Bodied - LOW VOC - Fast Setting - Solvent Cement with ISI Mark

- Compliant with ISI – IS14182 Standard
- Quality Product Designed for all grades and types of PVC, UPVC pipes and Fittings through 12”dia. Including Schedule 80.
- Primer is strongly recommended for more than 3” (90mm) diameter Pipe.
- Meets ASTM D-2564, Brookfield Viscosity minimum - 90 cP at 27°C
- Application for Residential plumbing, Industrial, Pool & Spa, Irrigation, drain, waste & vent system, Electrical conduit, PVC foam core pipe.
- Storage : Store in Cool & Dry place at Room Temp. Shelf Life : 1 Year
- Available in Packing :

PACK SIZE	25 ml Tube	100 ml Tube	50 ml	100 ml	250 ml	500 ml	1 ltr
UNITS PER CARTON	600	200	288	144	96	48	24



SEAL TITE PRIMER

CLEAR SOLVENT – Advisable For PVC, UPVC and CPVC Piping.

- Quality formulation for all classes and Schedule Through 24”(600 mm) diameter.
- Transperant liquid to Remove surface dirt, Degreasing and soften the joining surface rapidly for strong bond rigid PVC, UPVC and CPVC Pipes and Fittings.
- Meets ASTM F-656 Standard specifications,
- Strongly recommended for more than 3” (90mm) diameter Pipe
- Application for Potable water plumbing. Irrigation, Conduit, sewer. Drain, Waste and vent system
- Storage : Store in Cool & Dry place at Room Temp. Shelf Life : 3 Years
- Available in Packing :

PACK SIZE	118 ml (4 OZ)	237 ml (8 OZ)	473 ml (16 OZ)	948 ml (32 OZ)
UNITS PER CARTON	144	96	48	24

