

**TECHNICAL DATA SHEET**  
**RUBBER LUBRICANT**  
**Pipe Joint Lubricant**

**GENERAL DESCRIPTION :**

**SEAL TITE RUBBER LUBRICANT** is milky white, highly viscous, soft paste like water-based product. It aids in assembly of push on type joints to ensure correct fit. Seal Tite Rubber Gasket Lubricant doesn't support bacterial growth and it will not swell rubber components.

**APPLICATION :**

**SEAL TITE RUBBER LUBRICANT** is specially designed to lubricate rubber gaskets of pipelines including PVC and Soil pipes. It is ideal for SWR ring-fit, self-fit, sewer, drain piping system for low to non-pressure application.

**SPECIFICATION :**

APPEARANCE	Milky White
SPECIFIC GRAVITY	0.820 ± 0.010
BROOKFIELD VISCOSITY	Min. 30000 cP @ 73°F ± 2°F ( 23°± 1°C )

**AVAILABILITY :**

**SEAL TITE RUBBER LUBRICANT** is available in 100 gm , 250 gm, 500 gm Plastic Container.

**SHELF LIFE :**

Self life is 2 Year in tightly sealed containers. The date of Manufacturing and Expiry is stamped on the bottom of the container. Stability of the product is limited by the evaporation of the solvent when the container is opened. Evaporation of solvent will cause the cement to thicken and reduce its effectiveness. Adding of thinners to change viscosity is not recommended and may significantly change the properties of the cement.

**STORAGE :**

**SEAL TITE RUBBER LUBRICANT** shall be ideally stored in a cool and dry location. Keep away from children.

**QUALITY ASSURANCE :**

**SEAL TITE RUBBER LUBRICANT** is carefully evaluated to assure that consistent high quality is maintained by Gas chromatography, and additional in depth testing ensures each batch is manufactured according to standards. A batch identification code is stamped on bottom of each can and assures traceability of all materials used in the manufacturing.